

Dynojet Research Inc.

Nombre de la Prueba: CHEVY-C2-276TNB\RunFile_008.drf

Titulo de la Prueba: **CHEVY-C2-STOCK**Notas de la Prueba: **NIVEL STOCK**

Fecha de la Prueba: 07/01/2006 05:47:35 p.m.

RunFile_008.drf: 76.69°F 23.09in-Hg Humidad:37% SAE:1.34 Promedio de Marcha:62.50

Track	segs.	RPM x1000	HP	ft-lbs
0	0.28	2.1	N/A	N/A
1	1.40	2.2	26.32	62.82
2	2.25	2.3	28.26	64.53
3	3.06	2.4	30.63	67.02
4	3.83	2.5	34.15	71.74
5	4.55	2.6	37.08	74.90
6	5.24	2.7	40.21	78.22
7	5.91	2.8	42.81	80.30
8	6.57	2.9	45.39	82.21
9	7.21	3.0	47.83	83.74
10	7.85	3.1	49.59	84.02
11	8.49	3.2	51.08	83.83
12	9.12	3.3	52.48	83.52
13	9.77	3.4	53.88	83.24
14	10.42	3.5	54.26	81.43
15	11.08	3.6	55.35	80.75
16	11.77	3.7	55.21	78.37
17	12.46	3.8	55.54	76.76
18	13.18	3.9	55.47	74.70
19	13.93	4.0	54.72	71.85
20	14.69	4.1	55.92	71.63
21	15.46	4.2	56.47	70.61
22	16.22	4.3	57.61	70.36
23	16.98	4.4	59.62	71.16
24	17.74	4.5	61.66	71.96
25	18.50	4.6	62.71	71.60
26	19.26	4.7	64.32	71.87
27	20.03	4.8	64.81	70.91
28	20.81	4.9	65.53	70.23
29	21.60	5.0	65.63	68.94
30	22.41	5.1	65.11	67.05
31	23.24	5.2	64.72	65.37
32	24.06	5.3	67.65	67.04
33	24.89	5.4	69.99	68.07
34	25.72	5.5	70.36	67.19
MAX:	25.72	5.5	70.36	84.02
MIN:	0.28	2.1	26.32	62.82

Dynojet Research Inc.

Nombre de la Prueba: CHEVY-C2-276TNB\RunFile_003.drf

Titulo de la Prueba: **CHEVY-C2-N#2**Notas de la Prueba: **NIVEL #2**

Fecha de la Prueba: 07/01/2006 06:25:37 p.m.

RunFile_003.drf: 77.57°F 23.08in-Hg Humidad:36% SAE:1.34 Promedio de Marcha:62.52

Track	segs.	RPM x1000	HP	ft-lbs
0	0.3	2.2	N/A	N/A
1	1.5	2.3	30.44	69.50
2	2.25	2.4	33.31	72.90
3	2.96	2.5	36.38	76.43
4	3.64	2.6	39.61	80.02
5	4.28	2.7	42.63	82.93
6	4.92	2.8	45.44	85.24
7	5.53	2.9	48.05	87.02
8	6.14	3.0	49.96	87.46
9	6.75	3.1	51.76	87.68
10	7.35	3.2	53.69	88.11
11	7.97	3.3	54.58	86.86
12	8.58	3.4	55.85	86.28
13	9.21	3.5	56.50	84.78
14	9.86	3.6	56.92	83.05
15	10.52	3.7	57.14	81.11
16	11.19	3.8	57.55	79.54
17	11.88	3.9	57.87	77.93
18	12.59	4.0	58.20	76.42
19	13.29	4.1	59.83	76.65
20	14.01	4.2	60.51	75.67
21	14.72	4.3	61.90	75.61
22	15.43	4.4	63.48	75.77
23	16.14	4.5	65.81	76.81
24	16.85	4.6	67.10	76.61
25	17.56	4.7	68.44	76.48
26	18.28	4.8	69.61	76.17
27	19.00	4.9	70.67	75.75
28	19.73	5.0	72.16	75.80
29	20.46	5.1	72.55	74.72
30	21.20	5.2	73.65	74.39
31	21.95	5.3	74.44	73.77
32	22.68	5.4	76.45	74.36
33	23.44	5.5	76.87	73.40
34	24.21	5.6	76.58	71.82
35	25.01	5.7	76.54	70.53
36	25.83	5.8	75.68	68.53
37	26.68	5.9	74.64	66.44
38	27.56	6.0	73.11	63.99
MAX:	27.56	6	76.87	88.11